



PRODUCT-DETAILS

ACH580-01-062A-4

LV AC wall-mounted drive for HVAC, IEC: Pn 30 kW, 62 A, 400 V, UL: Pld 40 Hp, 52 A (ACH580-01-062A-4)



General Information	
Global Commercial Alias	ACH580-01-062A-4
Product ID	3AUA0000080523
ABB Type Designation	ACH580-01-062A-4
EAN	6438177305798
Catalog Description	LV AC wall-mounted drive for HVAC, IEC: Pn 30 kW, 62 A, 400 V, UL: Pld 40 Hp, 52 A (ACH580-01-062A-4)
Long Description	ACH580 HVAC drive offering has all key features built-in to control fans, pumps and compressors, and more complex equipment like air- handling units and chillers, ensuring smooth, energy-efficient operation of your HVAC systems in normal and mission-critical situations. The built-in features significantly reduce installation time and the intuitive control panel with an HVAC-specific primary settings menu and help assistants makes startup, commissioning and operation easy. The optional Bluetooth® capability enables the commissioning and monitoring of the drive from a distance. The ACH580-01 comes in IP21 enclosure and can be installed on the wall as standard. Also, IP55 and flange mounting units are available.

Ordering	
Customs Tariff Number	85044086
HS Code	850440 -- ELECTRICAL MACHINERY AND EQUIPMENT AND PARTS

THEREOF; SOUND RECORDERS AND REPRODUCERS, TELEVISION IMAGE AND SOUND RECORDERS AND REPRODUCERS, AND PARTS AND ACCESSORIES OF SUCH ARTICLES;Electrical transformers, static converters (for example, rectifiers) and inductors;Static converters	
Invoice Description	ACH580-01-062A-4 PN: 30 kW, IN: 62 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Weight	19.00 kg 44 lb
Product Net Depth / Length	257 mm 10.12 in
Product Net Height	636 mm 25.04 in
Product Net Width	203 mm 7.99 in
Package Level 1 Depth / Length	760.00 mm 31 in
Package Level 1 Height	428.00 mm 14 in
Package Level 1 Width	298.00 mm 11 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3-phase
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	4000 m 95
Sound dB (A)	70 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R4
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	BACNET CAN DeviceNet EtherNet/IP LON MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0

	RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Normal Use (I_n)	62 A
Output Current, Light-Overload Use (I_{LD})	58 A
Output Current, Heavy-Duty Use (I_{HD})	45 A
Output Power, Normal Use (P_n)	30 kW
Output Power, Light-Overload Use (P_{LD})	30 kW
Output Power, Heavy-Duty Use (P_{HD})	22.0 kW
	873 W
Apparent Power Output	43 kV-A
Efficiency Level	IE2
Standby Loss	19 W
Complete Drive Module Efficiency (IEC61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	247 W	90.2 %	0.6 %
0/50 %	322 W	93.2 %	0.7 %
0/100 %	574 W	93.8 %	1.3 %
50/25 %	270 W	94.6 %	0.6 %
50/50 %	370 W	96.1 %	0.9 %
50/100 %	683 W	96.4 %	1.6 %
90/50 %	430 W	97.5 %	1.0 %
90/100 %	873 W	97.4 %	2.0 %

Temperature Rating	Minimum -15 °C
--------------------	----------------

Technical UL

Output Current, Heavy-Duty Use (UL)	40 A
Output Current, Light-Overload Use (UL)	52 A
Output Power, Light-Overload Use (UL)	40 Hp

Certificates and Declarations

Declaration of Conformity - CE	3AXD10001818627
--------------------------------	-----------------

REACH Date	20250905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20240508
RoHS Declaration	3AXD10001818627
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Environmental

Global Warming	Distribution (Module A4) 4 kg CO ₂ eq
Potential GWP Total	End of Life (Modules C1-C4) 34 kg CO ₂ eq
	Installation (Module A5) 6 kg CO ₂ eq
	Manufacturing (Modules A1-A3) 310 kg CO ₂ eq
	Total 8319 kg CO ₂ eq
	Use (Modules B1-B7) 7965 kg CO ₂ eq
SCIP	596c7575-1ed1-48e9-be9a-d8fdd900606b Finland
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

External Classifications and Standards

ETIM 9	EC001857 - Frequency converter =< 1 kV
ETIM 10	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Categories

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for HVAC → ACH580-01 - Wall-mounted drive for HVAC

